

JTS Inflation Fans

Fabricated/assembled in-house using American-made components, sourced from Grainger and Dayton.

Durable, long-lasting, cost-efficient.



	JTS 20 Inch Fan	JTS 24 Inch Fan
Motor	½ Hp TEFC	¾ Hp TEFC
Fan Diameter	20" (50.8 cm)	24" (61 cm)
Blades	four (4)	four (4)
HxWxD inches (centimeters)	24x24x16* (61x61x40.6)	28x28x16 (71.1x71.1x40.6)
Weight	57 pounds (21.3 kg)	67 pounds (25 kg)
Voltage	110 V**	110 V**
Phase	60 Hz**	60 Hz**
Flow Rate CFM (m³/min)	4,675 (132.4)	6,860 (194.3)
Generator Draw (Amperage)	9 Amp	11 Amp
Cord Length	8 feet (2.4 m)	8 feet (2.4 m)

* 16" is TOTAL fan depth (nose extends 5" beyond 11" cabinet depth)

** can be converted to 220 V / 50 Hz (this reduces RPMs and increases inflation-time)



The ORIGINAL Safety Air Cushion

6101 Humphreys Street
Harahan, Louisiana 70123
United States of America

(504) 887-4714

SafetyProducts@JumpToSafety.net

www.JumpToSafety.net